

Package: vvtermttime (via r-universe)

November 3, 2024

Type Package

Title Interface for 'Semestry TermTime' Services

Version 0.0.1

Description Provides an R interface for interacting with the 'Semestry TermTime' services. It allows users to retrieve scheduling data from the API. see <https://github.com/vusaverse/vvtermttime/blob/main/openapi_7.7.0.pdf> for details.

URL <https://github.com/vusaverse/vvtermttime>,
<https://vusaverse.github.io/vvtermttime/>

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Imports httr, jsonlite, magrittr

Suggests knitr, rmarkdown

VignetteBuilder knitr

Repository <https://vusaverse.r-universe.dev>

RemoteUrl <https://github.com/vusaverse/vvtermttime>

RemoteRef HEAD

RemoteSha 66e51fef68ea85e0b8aa9a955aeaf5905e949dd9

Contents

authenticate	2
get_activities	3
get_activities_report_attr	3
get_activities_report_sche	4
get_activity_groups	4
get_activity_types	5

get_assessment_types	5
get_booking_types	6
get_buildings	6
get_campuses	7
get_capabilities	7
get_contact_requirements	8
get_courses	8
get_database	9
get_departments	9
get_modules	10
get_offers	10
get_report_booking	11
get_report_room	11
get_roombookings	12
get_rooms	12
get_room_relationships	13
get_schedule_rooms	13
get_staff	14
get_staff_groups	14
get_staff_pools	15
get_students	15
get_student_groups	16
get_student_group_maps	16
get_supergroups	17
get_timeframes	17
get_webhooks	18

Index**19**

authenticate	<i>Authenticate with Semestry Termtime API</i>
---------------------	--

Description

This function authenticates with the Semestry Termtime API by verifying the API key and base URL. It returns an authenticated Semestry object that can be used for subsequent API calls.

Usage

```
authenticate(api_key, base_url)
```

Arguments

api_key	The API key for Semestry.
base_url	The base URL of the Semestry API.

Value

An authenticated Semestry object.

get_activities	<i>Retrieve activity data from the Semestry API</i>
----------------	---

Description

This function sends a GET request to the activities endpoint of the Semestry API and retrieves the activity data.

Usage

```
get_activities(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved activity data from the API.

get_activities_report_attr	<i>Retrieve activity report attr from the Semestry API</i>
----------------------------	--

Description

This function sends a GET request to the report room endpoint of the Semestry API and retrieves the room booking data.

Usage

```
get_activities_report_attr(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved activity report data from the API.

`get_activities_report_sche`

Retrieve activity report schedule from the Semestry API

Description

This function sends a GET request to the report room endpoint of the Semestry API and retrieves the room booking data.

Usage

```
get_activities_report_sche(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved activity report data from the API.

`get_activity_groups`

Retrieve activity group data from the Semestry API

Description

This function sends a GET request to the activity groups endpoint of the Semestry API and retrieves the activity group data.

Usage

```
get_activity_groups(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved activity group data from the API.

```
get_activity_types      Retrieve activity type data from the Semestry API
```

Description

This function sends a GET request to the activity types endpoint of the Semestry API and retrieves the activity type data.

Usage

```
get_activity_types(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved activity type data from the API.

```
get_assessment_types   Retrieve assessment type data from the Semestry API
```

Description

This function sends a GET request to the assessment types endpoint of the Semestry API and retrieves the assessment type data.

Usage

```
get_assessment_types(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved assessment type data from the API.

get_booking_types *Retrieve booking type data from the Semestry API*

Description

This function sends a GET request to the booking types endpoint of the Semestry API and retrieves the booking type data.

Usage

```
get_booking_types(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved booking type data from the API.

get_buildings *Retrieve building data from the Semestry API*

Description

This function sends a GET request to the buildings endpoint of the Semestry API and retrieves the building data.

Usage

```
get_buildings(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved building data from the API.

get_campuses	<i>Retrieve campus data from the Semestry API</i>
--------------	---

Description

This function sends a GET request to the campuses endpoint of the Semestry API and retrieves the campus data.

Usage

```
get_campuses(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved campus data from the API.

get_capabilities	<i>Retrieve capability data from the Semestry API</i>
------------------	---

Description

This function sends a GET request to the capabilities endpoint of the Semestry API and retrieves the capability data.

Usage

```
get_capabilities(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved capability data from the API.

`get_contact_requirements`

Retrieve contact requirement data from the Semestry API

Description

This function sends a GET request to the contact requirements endpoint of the Semestry API and retrieves the contact requirement data.

Usage

```
get_contact_requirements(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved contact requirement data from the API.

`get_courses`

Retrieve course data from the Semestry API

Description

This function sends a GET request to the courses endpoint of the Semestry API and retrieves the course data.

Usage

```
get_courses(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved course data from the API.

Examples

```
## Not run:  
semestry <- authenticate_semestry()  
get_courses(semestry)  
  
## End(Not run)
```

get_database

Retrieve data from the Semestry API database endpoint

Description

This function sends a GET request to the database endpoint of the Semestry API and retrieves the data.

Usage

```
get_database(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved data from the API database.

get_departments

Retrieve department data from the Semestry API

Description

This function sends a GET request to the departments endpoint of the Semestry API and retrieves the department data.

Usage

```
get_departments(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved department data from the API.

<code>get_modules</code>	<i>Retrieve module data from the Semestry API</i>
--------------------------	---

Description

This function sends a GET request to the modules endpoint of the Semestry API and retrieves the module data.

Usage

```
get_modules(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved module data from the API.

<code>get_offers</code>	<i>Retrieve offers from the Semestry API</i>
-------------------------	--

Description

This function sends a GET request to the offers endpoint of the Semestry API and retrieves the offers.

Usage

```
get_offers(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved offers from the API.

Examples

```
## Not run:  
semestry <- authenticate_semestry()  
get_offers(semestry)  
  
## End(Not run)
```

get_report_booking *Retrieve booking report from the Semestry API*

Description

This function sends a GET request to the report booking endpoint of the Semestry API and retrieves the booking booking data.

Usage

```
get_report_booking(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved report booking data from the API.

get_report_room *Retrieve room report from the Semestry API*

Description

This function sends a GET request to the report room endpoint of the Semestry API and retrieves the room booking data.

Usage

```
get_report_room(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved report room data from the API.

`get_roombookings`

Retrieve room booking data from the Semestry API

Description

This function sends a GET request to the roombookings endpoint of the Semestry API and retrieves the room booking data.

Usage

```
get_roombookings(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved room booking data from the API.

`get_rooms`

Retrieve room data from the Semestry API

Description

This function sends a GET request to the rooms endpoint of the Semestry API and retrieves the room data.

Usage

```
get_rooms(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved room data from the API.

Examples

```
## Not run:  
semestry <- authenticate_semestry()  
get_rooms(semestry)  
  
## End(Not run)
```

get_room_relationships

Retrieve room relationship data from the Semestry API

Description

This function sends a GET request to the room relationships endpoint of the Semestry API and retrieves the room relationship data.

Usage

```
get_room_relationships(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved room relationship data from the API.

get_schedule_rooms

Retrieve schedule rooms data from the Semestry API

Description

This function sends a GET request to the schedule/rooms endpoint of the Semestry API and retrieves the schedule rooms data.

Usage

```
get_schedule_rooms(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved schedule rooms data from the API.

`get_staff`

Retrieve staff data from the Semestry API

Description

This function sends a GET request to the staff endpoint of the Semestry API and retrieves the staff data.

Usage

```
get_staff(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved staff data from the API.

Examples

```
## Not run:
semestry <- authenticate_semestry()
get_staff(semestry)

## End(Not run)
```

`get_staff_groups`

Retrieve staff group data from the Semestry API

Description

This function sends a GET request to the staff groups endpoint of the Semestry API and retrieves the staff group data.

Usage

```
get_staff_groups(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved staff group data from the API.

get_staff_pools *Retrieve staff pools from the Semestry API*

Description

This function sends a GET request to the staffpools endpoint of the Semestry API and retrieves the staff pools.

Usage

```
get_staff_pools(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved staff pools from the API.

get_students *Retrieve student data from the Semestry API*

Description

This function sends a GET request to the students endpoint of the Semestry API and retrieves the student data.

Usage

```
get_students(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved student data from the API.

Examples

```
## Not run:
semestry <- authenticate_semestry()
get_students(semestry)

## End(Not run)
```

get_student_groups *Retrieve student group data from the Semestry API*

Description

This function sends a GET request to the student groups endpoint of the Semestry API and retrieves the student group data.

Usage

```
get_student_groups(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved student group data from the API.

get_student_group_maps *Retrieve student group mappings from the Semestry API*

Description

This function sends a GET request to the studentgroupmaps endpoint of the Semestry API and retrieves the student group mappings data.

Usage

```
get_student_group_maps(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved student group maps from the API.

`get_supergroups`

Retrieve supergroup data from the Semestry API

Description

This function sends a GET request to the supergroups endpoint of the Semestry API and retrieves the supergroup data.

Usage

```
get_supergroups(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved supergroup data from the API.

`get_timeframes`

Retrieve timeframes data from the Semestry API

Description

This function sends a GET request to the timeframes endpoint of the Semestry API and retrieves the timeframes data.

Usage

```
get_timeframes(semestry, timeout = 30)
```

Arguments

semestry	An authenticated Semestry object.
timeout	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved timeframes data from the API.

`get_webhooks`

Retrieve webhook data from the Semestry API

Description

This function sends a GET request to the webhooks endpoint of the Semestry API and retrieves the webhook data.

Usage

```
get_webhooks(semestry, timeout = 30)
```

Arguments

<code>semestry</code>	An authenticated Semestry object.
<code>timeout</code>	The timeout duration for the GET request (default: 30 seconds).

Value

The retrieved webhook data from the API.

Index

authenticate, 2
get_activities, 3
get_activities_report_attr, 3
get_activities_report_sche, 4
get_activity_groups, 4
get_activity_types, 5
get_assessment_types, 5
get_booking_types, 6
get_buildings, 6
get_campuses, 7
get_capabilities, 7
get_contact_requirements, 8
get_courses, 8
get_database, 9
get_departments, 9
get_modules, 10
get_offers, 10
get_report_booking, 11
get_report_room, 11
get_room_relationships, 13
get_roombookings, 12
get_rooms, 12
get_schedule_rooms, 13
get_staff, 14
get_staff_groups, 14
get_staff_pools, 15
get_student_group_maps, 16
get_student_groups, 16
get_students, 15
get_supergroups, 17
get_timeframes, 17
get_webhooks, 18